

DDR4 GAMING **DELTA RGB**

THE POWER FROM TEAM GROUP
T-FORCE | DELTA RGB
T-FORCE GAMING DDR4
DELTA RGB

Pursuing the perfect revolution

Team Group T-FORCE gaming series once again released the all new luminous memory module – DELTA RGB. The R on the heat spreader represents Revolution, and also stands for creative concept with an uncompromised spirit. The heat spreader is built with lighter, thinner and high quality metal material. The colorful light changes make the hollow “R” on the front even more stereoscopic, and echo the ultra wide angle luminous area. The extraordinary Revolution will provide players a new experience never seen before.

Full color, dazzling and 120° ultra wide angle force flow lighting effect

DELTA RGB is using full color, dazzling RGB LED lighting with force flow effect. Like a Jedi holding the lightsaber, players can be invincible in the gaming world. T-FORCE LOGO is like a warrior's badge, standing still in the changing lights. The full frame, 120° ultra wide angle luminous area at the top emits colorful bright light. The color of the light changes smoothly to provide players an unparalleled visual feast, no matter it is day or night.



Asymmetric minimalist design

The one piece, geometric line design makes the heat spreader looks simple but energetic, and the Cubist style in the new art movement is also presented, which is a perfect combination of technology and aesthetics. The embossed lines on the surface not only increase the heat dissipation area and also effectively enhance cooling of the memory module, so the quality of the operation can be finely stabilized.

Support T-FORCE BLITZ / ASUS AURA SYNC GIGABYTE RGB Fusion / MSI Mystic Light Sync software

T-FORCE DELTA RGB offers full-color, variable, synchronized lighting. The lighting and synchronization are controlled with T-FORCE BLITZ (beta version)[1] or ASUS Aura Sync[2], and after being synchronized, there are 8 built-in light display modes to choose from. You may also control the lighting and some synchronization effects with GIGABYTE's RGB Fusion [3] or MSI's Mystic Light Sync[4]. Besides, you can express yourself by customizing your own lighting display. No matter which you choose, it is sure to look cool.



[1]: T-FORCE BLITZ (beta version) may be downloaded from the TEAMGROUP website or T-FORCE DELTA RGB webpage.

[2]: T-FORCE DELTA RGB supports Asus Aura Sync which can control the lighting effect and achieve complete synchronization of lighting effects.

[3/4]: T-FORCE DELTA RGB is compatible with GIGABYTE RGB FUSION /MSI Mystic Light Sync and some system lighting synchronization effects, but the system lighting synchronization functions with RGB FUSION will only be possible once GIGABYTE/ MSI updates its software.

The transmitting performance can be greatly increased with JEDEC RC 2.0

Using the latest customized JEDEC RC 2.0 circuit board to increase the distance between the power layer and the signal layer. Compared to ordinary memories, the transmitting signal is raised by 35%. There will be no interference between the power and the signal, and gets better performance. It completely releases the transmission of memory module, and offers players the ultimate sensation of overclocking and a highly stable overclocking memory module.



XMP2.0 1 step overclocking technology

DELTA RGB series support Intel XMP 2.0. It is only one step away to experience the high speed sensation of overclocking.



Ultra low working voltage Save energy up to 40%

With low working voltage 1.2~1.4V from DDR4 DELTA RGB , it is not only energy saving but it can also reduce the temperature and the heat generated to offer the high speed running memory a stable and long time operation.



QVL approved by motherboard manufacturers

Multiple compatibility verifications with mainstream DDR4 motherboards to make sure its stability with all motherboards on the QVL(Qualified Vendor List). Therefore, you wouldn't have to worry about compatibility issues when purchasing high speed memory.



Main Feature

- Full frame 120° ultra wide angle lighting
- Built in Force Flow RGB lighting effect
- Aluminum alloy heat spreader with asymmetric minimalist design
- Supports T-FORCE Blitz control (Beta version)
- Supports ASUS Aura Sync software synchronization
- Latest JEDEC RC 2.0 PCB
- Energy saving 1.2V~1.4V ultra low working voltage
- Supports XMP2.0 one click overclocking technology
- QVL approved by all mainstream motherboard manufacturers



Specification

Item	Specifications			
Series	DELTA RGB			
Module Type	288 Pin Unbuffered DIMM Non ECC			
Capacity	4GB / 8GB / 16GB / 4GBx2 / 8GBx2 / 16GBx2			
Tested Speed	2400	2666	3000	3200
Data transfer bandwidth	19,200 MB/s (PC4 19200)	21,300 MB/s (PC4 21300)	24,000 MB/s (PC4 24000)	25,600 MB/s (PC4 25600)
Tested Latency	CL15-17-17-35 CL16-16-16-39	CL15-17-17-35	CL16-18-18-38	CL16-18-18-38
Tested Voltage	1.2V	1.2V	1.35V	1.35V
Dimensions (mm)	49(H) x 147(L) x 7(W)mm			
Warranty	Lifetime Warranty			



Ordering Information

Color	Description	Light	Timings/Voltage	Capacity	Team P/N
Black	TEAM DELTA RGB UD-D4 2400	RGB	CL16-16-16-39 1.2V	4GB	TF3D44G2400HC1601
			CL16-16-16-39 1.2V	8GB	TF3D48G2400HC1601
			CL16-16-16-39 1.2V	16GB	TF3D416G2400HC1601
			CL15-17-17-35 1.2V	4GB	TF3D44G2400HC15B01
			CL15-17-17-35 1.2V	8GB	TF3D48G2400HC15B01
			CL15-17-17-35 1.2V	16GB	TF3D416G2400HC15B01
	TEAM DELTA RGB UD-D4 2666		CL15-17-17-35 1.2V	4GB	TF3D44G2666HC15B01
			CL15-17-17-35 1.2V	8GB	TF3D48G2666HC15B01
			CL15-17-17-35 1.2V	16GB	TF3D416G2666HC15B01
	TEAM DELTA RGB UD-D4 2400		CL16-16-16-39 1.2V	4GBx2	TF3D48G2400HC16DC01
			CL16-16-16-39 1.2V	8GBx2	TF3D416G2400HC16DC01
			CL16-16-16-39 1.2V	16GBx2	TF3D432G2400HC16DC01
			CL15-17-17-35 1.2V	4GBx2	TF3D48G2400HC15BDC01
			CL15-17-17-35 1.2V	8GBx2	TF3D416G2400HC15BDC01
			CL15-17-17-35 1.2V	16GBx2	TF3D432G2400HC15BDC01
	TEAM DELTA RGB UD-D4 2666		CL15-17-17-35 1.2V	4GBx2	TF3D48G2666HC15BDC01
			CL15-17-17-35 1.2V	8GBx2	TF3D416G2666HC15BDC01
			CL15-17-17-35 1.2V	16GBx2	TF3D432G2666HC15BDC01
	TEAM DELTA RGB UD-D4 3000		CL16-18-18-38 1.35V	4GBx2	TF3D48G3000HC16CDC01
			CL16-18-18-38 1.35V	8GBx2	TF3D416G3000HC16CDC01
			CL16-18-18-38 1.35V	16GBx2	TF3D432G3000HC16CDC01
	TEAM DELTA RGB UD-D4 3200		CL16-18-18-38 1.35V	8GBx2	TF3D416G3200HC16CDC01
			CL16-18-18-38 1.35V	16GBx2	TF3D432G3200HC16CDC01

Ordering Information

Color	Description	Light	Timings/Voltage	Capacity	Team P/N
White	TEAM DELTA RGB UD-D4 2400	RGB	CL16-16-16-39 1.2V	4GB	TF4D44G2400HC1601
			CL16-16-16-39 1.2V	8GB	TF4D48G2400HC1601
			CL16-16-16-39 1.2V	16GB	TF4D416G2400HC1601
			CL15-17-17-35 1.2V	4GB	TF4D44G2400HC15B01
			CL15-17-17-35 1.2V	8GB	TF4D48G2400HC15B01
			CL15-17-17-35 1.2V	16GB	TF4D416G2400HC15B01
	TEAM DELTA RGB UD-D4 2666		CL15-17-17-35 1.2V	4GB	TF4D44G2666HC15B01
			CL15-17-17-35 1.2V	8GB	TF4D48G2666HC15B01
			CL15-17-17-35 1.2V	16GB	TF4D416G2666HC15B01
	TEAM DELTA RGB UD-D4 2400		CL16-16-16-39 1.2V	4GBx2	TF4D48G2400HC16DC01
			CL16-16-16-39 1.2V	8GBx2	TF4D416G2400HC16DC01
			CL16-16-16-39 1.2V	16GBx2	TF4D432G2400HC16DC01
			CL15-17-17-35 1.2V	4GBx2	TF4D48G2400HC15BDC01
			CL15-17-17-35 1.2V	8GBx2	TF4D416G2400HC15BDC01
			CL15-17-17-35 1.2V	16GBx2	TF4D432G2400HC15BDC01
	TEAM DELTA RGB UD-D4 2666		CL15-17-17-35 1.2V	4GBx2	TF4D48G2666HC15BDC01
			CL15-17-17-35 1.2V	8GBx2	TF4D416G2666HC15BDC01
			CL15-17-17-35 1.2V	16GBx2	TF4D432G2666HC15BDC01
	TEAM DELTA RGB UD-D4 3000		CL16-18-18-38 1.35V	4GBx2	TF4D48G3000HC16CDC01
			CL16-18-18-38 1.35V	8GBx2	TF4D416G3000HC16CDC01
			CL16-18-18-38 1.35V	16GBx2	TF4D432G3000HC16CDC01
	TEAM DELTA RGB UD-D4 3200		CL16-18-18-38 1.35V	8GBx2	TF4D416G3200HC16CDC01
			CL16-18-18-38 1.35V	16GBx2	TF4D432G3200HC16CDC01

Above technical information is based on industry standard data and tested to be reliable. However, Team makes no warranty, either expressed or implied, as to its accuracy and assumes no liability in connection with the use of this product.

Team reserves the right to make changes in specifications at any time without prior notice.