



ZEUS DDR4

ZEUS DDR4

ZEUS, the king of the gods, symbolizes thunder and is armed with a powerful Lighting Bolt. T-FORCE's latest gaming memory ZEUS has a massive 32GB single stick memory and various of frequencies, and it is also tested for complete compatibility and stability. With this powerful weapon in hand, gamers can be invincible in the gaming world.

Main Feature

- Lightning Bolt design element
- Born for gaming
- High quality IC with stable performance
- Support O.C. Profile
- Reliable compatibility



Specification

| Module Type | DDR4 288 pin Non-ECC Unbuffered DIMM | | | |
|-------------------------|---|---|---|---|
| Frequency | 2666 | 3000 | 3200 | 3200 |
| Latency | CL19-19-19-43 | CL16-18-18-38 | CL20-22-22-46 | CL16-20-20-40 |
| Capacity | 8GB / 8GBx2 16GB / 16GBx2 32GB / 32GBx2 | 8GB / 8GBx2 16GB / 16GBx2 32GB / 32GBx2 | 8GB / 8GBx2 16GB / 16GBx2 32GB / 32GBx2 | 8GB / 8GBx2 16GB / 16GBx2 32GB / 32GBx2 |
| Data Transfer Bandwidth | 21,328 MB/s (PC4 21300) | 24,000 MB/s (PC4 24000) | 25,600 MB/s (PC4 25600) | 25,600 MB/s (PC4 25600) |
| Voltage | 1.2V | 1.35V | 1.2V | 1.35V |
| Dimensions | 32(H) x 134(L)mm | | | |
| Warranty | Lifetime warranty | | | |

Ordering Information

| Frequency | CAS Latency/Voltage | Capacity | Team P/N |
|-----------------------|---------------------|----------|---------------------|
| DDR4-2666 (PC4 21300) | CL19-19-19-43 1.2V | 8GB | TTZD48G2666HC1901 |
| | | 16GB | TTZD416G2666HC1901 |
| | | 32GB | TTZD432G2666HC1901 |
| DDR4-3000 (PC4 24000) | CL16-18-18-38 1.35V | 8GB | TTZD48G3000HC16C01 |
| | | 16GB | TTZD416G3000HC16C01 |
| | | 32GB | TTZD432G3000HC16C01 |
| DDR4-3200 (PC4 25600) | CL20-22-22-46 1.2V | 8GB | TTZD48G3200HC2001 |
| | | 16GB | TTZD416G3200HC2001 |
| | | 32GB | TTZD432G3200HC2001 |
| | CL16-20-20-40 1.35V | 8GB | TTZD48G3200HC16F01 |
| | | 16GB | TTZD416G3200HC16F01 |
| | | 32GB | TTZD432G3200HC16F01 |

| Frequency | CAS Latency/Voltage | Capacity | Team P/N |
|-----------------------|---------------------|----------|-----------------------|
| DDR4-2666 (PC4 21300) | CL19-19-19-43 1.2V | 8GBx2 | TTZD416G2666HC19DC01 |
| | | 16GBx2 | TTZD432G2666HC19DC01 |
| | | 32GBx2 | TTZD464G2666HC19DC01 |
| DDR4-3000 (PC4 24000) | CL16-18-18-38 1.35V | 8GBx2 | TTZD416G3000HC16CDC01 |
| | | 16GBx2 | TTZD432G3000HC16CDC01 |
| | | 32GBx2 | TTZD464G3000HC16CDC01 |
| DDR4-3200 (PC4 25600) | CL20-22-22-46 1.2V | 8GBx2 | TTZD416G3200HC20DC01 |
| | | 16GBx2 | TTZD432G3200HC20DC01 |
| | | 32GBx2 | TTZD464G3200HC20DC01 |
| | CL16-20-20-40 1.35V | 8GBx2 | TTZD416G3200HC16FDC01 |
| | | 16GBx2 | TTZD432G3200HC16FDC01 |
| | | 32GBx2 | TTZD464G3200HC16FDC01 |

※The frequency and stability of the overclocking memory when automatic reading of the overclocking value (XMP or D.O.C.P) is turned on will vary depending on the difference between the motherboard and CPU.

※We reserve the right to modify product specifications without prior notice.